


Navigation and Ancillary Information Facility

"Comments" In SPICE Kernels

Also known as "meta-data"


April 2023



What are Comments?

Navigation and Ancillary Information Facility

- Comments, also called "meta-data," are information that describe the context of kernel data, i.e. "data about data"
- Comments are provided inside kernels as plain text (prose)
- Examples of uses for comments:
 - Data descriptions
 - "This file contains representations of the trajectories for bodies X, Y and Z over the interval from launch to landing"
 - Data accuracy comments
 - Data pedigree
 - » How and by whom the kernel was created
 - The program(s) and/or steps used in creation
 - · Contact information for user's questions
 - email address
 - phone numbers
 - » Data sources used as inputs when creating the kernel
 - Intended kernel usage
 - Names of companion files




Where are Comments Stored?

Navigation and Ancillary Information Facility

- Binary kernels contain a reserved "comment area" to hold comments
- Text kernels have comments interleaved with the data
 - Comments may be placed at the beginning of the text kernel, before any data, and ...
 - Comments may be inserted between blocks of data using \begintext and \begindata as start and end markers:

```
\begintext
Some comments
\begindata
Some data
```



Adding Comments to Kernels

Navigation and Ancillary Information Facility

Binary Kernels


- Use the commnt utility program, available in the Toolkit
- Include comment information at the time of kernel creation using SPICE APIs (subroutines)

Text Kernels

- Use a text editor
 - » Begin comment sections with a "\begintext" marker, placed alone on a line
 - (The marker is not needed for comments occurring before any data)
 - » End comment sections with a "\begindata" marker, placed alone on a line
 - (The marker is not needed if there are no data following the comments)

Restrictions

- For both binary and text kernels
 - » Comment line length limit is 255 characters. However, NAIF recommends using no more than 80 characters per line as this makes your comments far more readable!
 - » Use only printing characters (ASCII 32 126)
 - » Manipulating binary kernel comments requires the kernel be in the native binary format for the machine being used
- For text kernels
 - » Refer to "Kernel Required Reading" (kernel.reg) for details



Viewing Comments in Kernels


Navigation and Ancillary Information Facility

Binary kernels:

- Use either the commnt or spacit utility program
 - » Both are available in all Toolkits

Text kernels:


- Use any available text file utility, such as:
 - » more, cat, vi, emacs
 - » Notepad, TextEdit, BBEdit, Word, etc.




Viewing Comments in Binary Kernels

Navigation and Ancillary Information Facility

This example shows reading the comments in an SPK file using the "commnt" utility program





Viewing Comments in Text Kernels

Navigation and Ancillary Information Facility

This example show use of the unix "more" processor to show some of the comments at the beginning of a text kernel.

